

Strength engineered. Excellence delivered.

CURING AGENT

WAX BASED CURING AGENT

Curing Agent is a wax based curing agent formulated to form a clear, continuous membrane on concrete surfaces. It prevents rapid moisture loss during the early stages of curing, ensuring proper cement hydration, improved strength development and enhanced durability.

ADVANTAGES

- ✓ High curing efficiency
- ✓ Reduces premature moisture loss
- ✓ Improves concrete strength
- ✓ Minimizes plastic shrinkage cracks
- ✓ Easy spray application
- ✓ Cost-effective solution
- ✓ Compatible with paints, renders & plasters

RECOMMENDED USES



Concrete construction



Concrete repairs



Grouting works

PHYSICAL PROPERTIES*

PROPERTY	TYPICAL RESULTS
Appearance	White liquid
Appearance when applied	Clear
Curing efficiency	> 90%
Touch dry	4 hours at 25°C
Recoat time	6 to 18 hours

* The above properties are average laboratory values.



PACKING

Curing Agent is available in 5 litre and 20 litre pack.



THEORETICAL COVERAGE

4 – 5 m² per litre per coat.
Minimum two coats recommended.

Actual coverage will depend on surface profile, porosity and site conditions.



SHELF LIFE

12 months when stored in cool dry environment in factory packed unopened containers between 5°C – 25°C.



PRECAUTIONS

- ✓ Do not add any thinner or solvent
- ✓ Avoid excessive application
- ✓ Avoid skin contact
- ✓ Do not dispose into water drains

CURING AGENT

PREMIUM WAX-BASED CURING AGENT



PRODUCT DESCRIPTION

Adhveya Curing Agent is a high-performance wax-based curing agent specially formulated to form a clear, continuous protective membrane on concrete surfaces. It effectively prevents rapid moisture loss during the early stages of curing, ensuring proper cement hydration, improved strength development and enhanced durability. Its advanced wax emulsion technology makes it ready to use, easy to apply and provides a cost-effective solution for all types of concrete construction.



ADVANTAGES

- ✓ High Curing Efficiency
- ✓ Improves Concrete Strength
- ✓ Reduces Premature Moisture Loss
- ✓ Minimizes Plastic Shrinkage Cracks
- ✓ Easy Spray Application
- ✓ Cost-Effective Solution
- ✓ Compatible with Paints, Renders & Plasters
- ✓ Improves Concrete Durability



TECHNICAL PROPERTIES (Typical Values)

PROPERTY	TYPICAL VALUE
Appearance	White Liquid
Appearance when applied	Clear
Curing efficiency	> 90%
Touch dry	4 hours at 25°C
Coverage	4 – 5 m ² per litre per coat
Recommended coats	Minimum two coats
Application method	Low Pressure Spray
Packaging	5 L & 20 L Packs
Shelf life	12 Months

*Actual coverage may vary depending on the surface texture and porosity.



PRECAUTIONS

- ✓ Do not add any thinner or solvent.
- ✓ Avoid excessive application.
- ✓ Avoid skin contact.
- ✓ Do not dispose into water drains.



PACKAGING

Available in:



5 Litre Pack



20 Litre Pack



STORAGE & SHELF LIFE

SHELF LIFE

12 months from the date of manufacture when stored in unopened original containers.

STORAGE

Store in a cool, dry place away from direct sunlight, moisture and frost. Keep containers tightly closed after use.



HEALTH & SAFETY

Wear suitable protective gloves and safety goggles during handling and application. Avoid contact with skin and eyes. In case of accidental contact, rinse immediately with plenty of clean water. If swallowed, do not induce vomiting and seek immediate medical attention. Refer to the Material Safety Data Sheet (MSDS) for complete handling and safety information.



RECOMMENDED USES



Concrete Construction



Concrete Repairs



Grouting Works



Residential & Commercial Construction



Concrete Slabs & Floors



Roads & Pavements



Bridges & Infrastructure



Precast Concrete Elements



SURFACE PREPARATION

Ensure the surface is clean, dry and free from dust, dirt, oil, grease, laitance, paint, curing compounds and other contaminants. The concrete surface should be sound and ready for application.



APPLICATION INSTRUCTIONS

1

STIR WELL BEFORE USE

Stir the container thoroughly before application to ensure uniform consistency.

2

APPLY

Apply uniformly using a low pressure spray system as soon as surface water has evaporated from freshly placed concrete.

3

UNIFORM COVERAGE

Ensure complete and continuous coverage for maximum curing efficiency.



MANUFACTURED BY:

ADHVEYA DRYMIX INDIA PVT LTD

KUBER INDUSTRIAL PARK

VALSAD, GUJARAT, INDIA



adhveya@gmail.com



www.adhveya.com | www.adhveya.in